

LITHIUM IRON PHOSPHATE (LIFEPO4) BATTERY

LP2800 Series

5.12/10.24/15.36KWH | WiFi | IP65

The LP2800 Series wall mounted Lithium battery (LiFePO4 Battery) solutions are highly integrated, deep cycle backup power solutions for your solar home energy storage system. Energy capacities ranging 5120Wh,10240Wh or 15360Wh with rich experience and advanced techniques, the product has the features of the fashionable design, high energy, high power density, long service life, and easiness of installation and expansion.



- Floor-mounted/ Wall-mounted
- Standard warranty: 10 years
- Large capacity, high power output
- Safest lithium iron phosphate battery cell with high energy density
- 10 Units in parallel maxium
- IP65 protection for both indoor and outdoor use
- Support CAN & RS485 communication with mainstream inverters
- Easy-To-Read monitoring
- Integrated battery management system (BMS)
- Built-in WiFi Smart Module
- Battery parallel kit can be used to expand battery capacity more conveniently (optional; max. 4pcs)

Application



Technical Data	LP28-48100	LP28-48200	LP28-48300
ELECTRICAL			
Nominal Voltage	51.2V		
Nominal Capacity	100Ah	200Ah	300Ah
Operating Voltage Range	43.2 ~ 56.8V		
Max. Charging Current	100A		
Max. Output Power	5KW	6KW	10KW
GENERAL			
Nominal Energy	5120Wh	10240Wh	15360Wh
Usable Energy	5120Wh	10240Wh	15360Wh
Scalability	Max. 10 in parallel (51.2kWh)	Max. 10 in parallel (102.4kWh)	Max. 10 in parallel (153.6kWh)
Design life	10+ Years at 25°C	10+ Years at 25°C	10+ Years at 25°C
Cycles life	>6000 at 25°C	>6000 at 25°C	>6000 at 25°C
OPERATING			
Charge Temperature	0~50°C		
Discharge Temperature	-20~55°C		
Storage Temperature	-20~45°C		
Humidity	5%~95% RH (No Condensation)		
Altitude	≤ 4000m		
Ingress Protection	IP65		
Install location	Indoor or outdoor without sunlight exposure		
Installation Mode	Floor-mounted/ Wall-mounted	Floor-mounted	Floor-mounted
Communication Interface	CAN/ RS485/ WIFI/ BLE		
Compatible Inverters	MUST, Victron, Goodwe, Growatt, Solis, Sofar, Deye, Voltronic, SMA, Luxpower		
Warranty	10 years		
MECHANICAL			
Machine Dimension (W*H*D) (mm)	500*525*150	500*865*150	500*893*250
Package Dimension (W*H*D) (mm) (wooden box)	/	/	/
N.W (kg)	≈51	≈98	/
G.W (kg) (wooden box)	/	/	/
* Variations in dimensions and weights may occur due to production batches.			
CERTIFICATION & STANDARDS			
UN38.3, EN 61000-6-1, EN 61000-6-3, IEC62619			